Product data sheet Characteristics

WMS332R

switch - 3 pole 32A 415V SA rvrsg cast aluminium material. tested to ac3 & ac23



Main		
Range of product	Wilco	
	Series A	
Product brand	Clipsal	
Device presentation	Basic element with complete housing	

Complementary

Complementary		
Switch function	3-pole	
Control type	Rotary knob	
Number of poles	3	
Device mounting	Base mounting	
Fixing mode	By screws	
Material	Cast aluminium	
Local signalling	without	
[Ue] rated operational voltage	415 V AC	
Rated current	32 A	
Marking	ON-OFF	
Marking location	Marking on surface	

Offer Sustainability

	Circularity Profile	No need of specific recycling operations
	EU RoHS Directive	Compliant EEU RoHS Declaration
	Office Oddital lability	

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherenced as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the documentation is not be used to perform the appropriate and complete risk analysis, evaluation of the products with respect to the relevant specific application or use thereof. Neither Schmeider Electric Industries SAS nor any of its affiliates or substitatives shall be responsible or liable for misuse of the information contained herein.