# **PHILIPS** Lighting



## TORNADO

### TORNADO 20W CDL E27 220-240V 1PF/6

The Helix range is a twist-shape compact fluorescent lamp, with optimal light distribution. It is available in 11W, 15W, 20W and 23W (25W), with lumen equivalence of 60W, 75W, 100W and 125W incandescent light bulb. It is also available in two color temperatures: warm white (2700K) and cool daylight (6500K). It is available in both 220-240V and 120-127V and able to operate under a wide voltage range (Power supply fluctuation). It consumes up to 80% less energy than the incandescent light bulb and lasts for 3 years.

#### Warnings and Safety

- Breaking a lamp is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a closed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- Compact fluorescent lamps have to be treated as special waste, they must be taken to your local waste facilities for recycling. The European Lighting Industry has set up an infrastructure, capable of recycling mercury, other metals, glass etc.

#### **Product data**


neral information		Chromaticity Coordinate X (Nom)	313
ap-Base	E27 [ E27]	Chromaticity Coordinate Y (Nom)	337
Nominal Lifetime (Nom)	8000 h	Correlated Color Temperature (Nom)	6500 K
Switching Cycle	5000X	Luminous Efficacy (rated) (Nom)	61 lm/W
ated Lifetime (Hours)	8000 h	Color Rendering Index (Nom)	80
		LLMF At End Of Nominal Lifetime (Nom)	70 %
Light technical			
Color Code	865 [ CCT of 6500K]	Operating and electrical	
uminous Flux (Nom)	1200 lm	Input Frequency	50 or 60 Hz
uminous Flux (Rated) (Nom)	1200 lm	Power (Nom)	20 W
Color Designation	Cool Daylight	Lamp Current (Nom)	150 mA
umen Maintenance 2000 h (Nom)	85 %	Starting Time (Nom)	0.3 s
umen Maintenance 5000 h (Nom)	75 %	Warm Up Time to 60% Light (Min)	5 s

#### TORNADO

Warm Up Time to 60% Light (Max)	60 s
Power Factor (Nom)	0.6
Voltage (Nom)	220-240 V
Controls and dimming	
Dimmable	No
Mechanical and housing	
Bulb Shape	Spiral
Approval and application	
Mercury (Hg) Content (Nom)	1.5 mg
Energy Consumption kWh/1000 h	20 kWh

871829113813600		
TORNADO 20W CDL E27 220-240V 1PF/6		
8718291138136		
929689848405		
1		
6		
929689848405		
0.065 kg		

#### **Dimensional drawing**



TORNADO 20W CDL E27 220-240V 1PF/6





© 2022 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.