



Pan-Steel® MLT2S-CP316 Cable Tie, SS 316, Standard, 2" Dia., PK100

MLT2S-CP316

The MLT2S-CP316 self-locking cable tie speeds up installation with a unique self-locking head design that locks into place at any part along the tie body. The smooth surfaces and rounded edges assure cable protection and worker safety. Provides a strong, durable method of cabling bundle and can be used in a wide range of indoor, outdoor, and underground applications.

Specifications

Product Type	Cable Tie
Sub Brand	Pan-Steel®
Color	Metallic
Environment	Harsh
Material	Stainless Steel Type 316
Resistance Properties	UV-Resistant
Overall Length (In.)	7.9
Overall Length (mm)	201
Body Width (In.)	0.18
Body Width (mm)	4.6
Body Thickness (In.)	0.01
Body Thickness (mm)	0.25
Maximum Bundle Diameter (In.)	2
Maximum Bundle Diameter (mm)	51
Minimum Bundle Diameter (In.)	0.5
Minimum Bundle Diameter (mm)	12.7
Minimum Loop Tensile Strength (N)	890
Minimum Loop Tensile Strength (lb)	200
Maximum Operating Temperature (°C)	538
Maximum Operating Temperature (°F)	1000
Minimum Operating Temperature (°C)	-60
Minimum Operating Temperature (°F)	-76
Minimum Installation Temperature (°C)	-60
Minimum Installation Temperature (°F)	-76
Standards Met	UL E56854,CE,ABS,GL,SAE,BV,LR,DNV
Military Cross Reference Number	M23190/3-1
For Use With	GS4MT-E, HTMT, PPTMT, ST2MT

Specifications (continued)

Application	Harsh Environment
Part Features	Reduces the number of installation steps required to provide lowest installed cost

Packaging Detail

UPC	07498354399
Std. Pkg. Qty.	100
Std. Pkg. Volume (cf)	0.0154
Std. Ctn. Qty.	500
Std. Ctn. Volume (cf)	0.0768