



Pan-Steel® MLT4H-LP316 Cable Tie, SS 316, Heavy, 4" Dia., PK50

MLT4H-LP316

The MLT4H-LP316 self-locking cable tie speeds up installation with a unique self-locking head design that locks into place at any part of the tie body. The smooth surfaces and rounded edges assure cable protection and worker safety while providing a strong, durable method of cabling bundle. The MLT4H-LP316 cable tie can be used in a wide range of indoor, outdoor, and underground applications. Color Stainless Steel.

Specifications

Product Type	Cable Tie
Sub Brand	Pan-Steel®
Color	Metallic
Environment	Harsh
Material	Stainless Steel Type 316
Resistance Properties	UV-Resistant
Overall Length (In.)	14.3
Overall Length (mm)	362
Body Width (In.)	0.31
Body Width (mm)	7.9
Body Thickness (In.)	0.01
Body Thickness (mm)	0.3
Maximum Bundle Diameter (In.)	4
Maximum Bundle Diameter (mm)	102
Minimum Bundle Diameter (In.)	0.5
Minimum Bundle Diameter (mm)	12.7
Minimum Loop Tensile Strength (N)	2000
Minimum Loop Tensile Strength (lb)	450
Maximum Operating Temperature (°C)	538
Maximum Operating Temperature (°F)	1000
Minimum Operating Temperature (°C)	-60
Minimum Operating Temperature (°F)	-76
Minimum Installation Temperature (°C)	-60
Minimum Installation Temperature (°F)	-76
Standards Met	UL E56854,CE,ABS,GL,SAE,BV,LR,DNV,USCG
Military Cross Reference Number	M23190/3-6

Specifications (continued)

For Use With	GS4MT-E, HTMT, PPTMT, ST2MT
Application	Harsh Environment

Packaging Detail

UPC	07498354388
Std. Pkg. Qty.	50
Std. Pkg. Volume (cf)	0.0238
Std. Ctn. Qty.	250
Std. Ctn. Volume (cf)	0.1191