



Pan-Ty® PLT2S-C3 Cable Tie, Orange, PA6.6, 7.4"L, 50lb, PK100

PLT2S-C3

Panduit PLT2S-C3 Locking Cable Ties are designed to satisfy the needs of mil spec applications, while delivering consistent performance and reliability. Featuring a curved tip to allow for easy pick up from flat surfaces and faster initial threading. Standard cross section, 7.4" (188mm) length. Made of Nylon 6.6, are orange in color and come in packages of 100.

Specifications

Material Description	Nylon 6.6 ()
Product Type	Premium Cable Tie
Color	Orange
Environment	Indoor
Material	Nylon 6.6
Overall Length (In.)	7.4
Overall Length (mm)	188
Body Width (In.)	0.19
Body Width (mm)	4.8
Body Thickness (In.)	0.052
Body Thickness (mm)	1.3
Maximum Bundle Diameter (In.)	1.88
Maximum Bundle Diameter (mm)	47.8
Minimum Bundle Diameter (In.)	0.06
Minimum Bundle Diameter (mm)	1.5
Minimum Loop Tensile Strength (N)	222
Minimum Loop Tensile Strength (lb)	50
Maximum Operating Temperature (°C)	85
Maximum Operating Temperature (°F)	185
Minimum Operating Temperature (°C)	-60
Minimum Operating Temperature (°F)	-76
Minimum Installation Temperature (°C)	-20
Minimum Installation Temperature (°F)	-4
Standards Met	CSA Certified, UL Recognized (File #E56854), UL 62275 Compliant (Type 2S, 21S), RoHS Compliant
Military Cross Reference Number	MS3367-1-3
For Use With	GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PPTS, PTH, STS2, STH2

Specifications (continued)

Part Features	One-piece locking wedge for consistent performance and reliability. Low thread force and high loop tensile strength.
---------------	--

Packaging Detail

UPC	07498354759
Std. Pkg. Qty.	100
Std. Pkg. Volume (cf)	0.0321
Std. Ctn. Qty.	1000
Std. Ctn. Volume (cf)	0.3207