



Pan-Ty® PLT2S-C59 Cable Tie, Fluor Pink, PA6.6, 7.4"L, 50lb, PK100

PLT2S-C59

Pan-Ty® locking tie, standard cross section, 7.4 (188mm) length, nylon 6.6, fluorescent pink, standard package.

Specifications

Material Description	Nylon 6.6 ()
Product Type	Premium Cable Tie
Color	Fluorescent Pink
Environment	Indoor
Material	Nylon 6.6
Overall Length (In.)	7.4
Overall Length (mm)	188
Body Width (In.)	0.19
Body Width (mm)	4.8
Body Thickness (In.)	0.052
Body Thickness (mm)	1.3
Maximum Bundle Diameter (In.)	1.88
Maximum Bundle Diameter (mm)	47.8
Minimum Bundle Diameter (In.)	0.06
Minimum Bundle Diameter (mm)	1.5
Minimum Loop Tensile Strength (N)	222
Minimum Loop Tensile Strength (lb)	50
Maximum Operating Temperature (°C)	85
Maximum Operating Temperature (°F)	185
Minimum Operating Temperature (°C)	-60
Minimum Operating Temperature (°F)	-76
Minimum Installation Temperature (°C)	-20
Minimum Installation Temperature (°F)	-4
Standards Met	RoHS Compliant
For Use With	GTS-E, GS2B-E, GTH-E, GS4H-E, PTS, PTH
Application	General
Part Features	One-piece locking wedge for consistent performance and reliability. Low thread force and high loop tensile strength.

Packaging Detail

UPC	07498334286
Std. Pkg. Qty.	100
Std. Pkg. Volume (cf)	0.0306
Std. Ctn. Qty.	1000
Std. Ctn. Volume (cf)	0.3060