



Pan-Ty® PLT7LH-L Cable Tie, PA6.6, 24.7"L, 120lb, PK50

PLT7LH-L

Panduit PLT7LH-L Locking Cable Ties are designed to satisfy the needs of general applications, while delivering consistent performance and reliability. Featuring a curved tip to allow for easy pick up from flat surfaces and faster initial threading. Light-Heavy cross section, 24.7" (627mm) length. Made of Nylon 6.6, are natural in color and come in packages of 50.

Specifications

Material Description	Nylon 6.6 ()
Product Type	Premium Cable Tie
Color	Natural
Environment	Indoor
Material	Nylon 6.6
Overall Length (In.)	24.7
Overall Length (mm)	627
Body Width (In.)	0.3
Body Width (mm)	7.6
Body Thickness (In.)	0.075
Body Thickness (mm)	1.9
Maximum Bundle Diameter (In.)	7
Maximum Bundle Diameter (mm)	178
Minimum Bundle Diameter (In.)	0.188
Minimum Bundle Diameter (mm)	4.8
Minimum Loop Tensile Strength (N)	534
Minimum Loop Tensile Strength (lb)	120
Maximum Operating Temperature (°C)	85
Maximum Operating Temperature (°F)	185
Minimum Operating Temperature (°C)	-60
Minimum Operating Temperature (°F)	-76
Minimum Installation Temperature (°C)	-20
Minimum Installation Temperature (°F)	-4
Standards Met	UL 62275 Compliant (Type 2, 21), UL Recognized (File #E56854), CSA Certified, RoHS Compliant
For Use With	GTH-E, GS4H-E, GS4EH-E, PTH, STH2, ST3EH
Part Features	One-piece locking wedge for consistent performance and reliability. Low thread force and high loop tensile strength.

Packaging Detail

UPC	07498354170
Std. Pkg. Qty.	50
Std. Pkg. Volume (cf)	0.1453
Std. Ctn. Qty.	500
Std. Ctn. Volume (cf)	1.4527