



Pan-Ty® PLT8EH-Q0 Cable Tie, Black, UV PA6.6, 28.3"L, 250lb, PK25

PLT8EH-Q0

Panduit PLT8EH-Q0 Lashing Cable Ties are ideal for heavy duty applications. Extra-Heavy cross section, 28.3" (719mm) length. For Indoor or outdoor use, made of Weather Resistant Nylon 6.6 with high resistance to ultraviolet light, are black in color and come in packages of 25.

Specifications

Material Description	Nylon 6.6 (UV-Resistant, Weather-Resistant)
Product Type	Premium Cable Tie
Color	Black
Environment	Indoor/Outdoor
Material	Nylon 6.6
Resistance Properties	UV-Resistant, Weather-Resistant
Overall Length (In.)	28.3
Overall Length (mm)	719
Body Width (In.)	0.5
Body Width (mm)	12.7
Body Thickness (In.)	0.085
Body Thickness (mm)	2.2
Maximum Bundle Diameter (In.)	8
Maximum Bundle Diameter (mm)	203.2
Minimum Bundle Diameter (In.)	2.5
Minimum Bundle Diameter (mm)	63.5
Minimum Loop Tensile Strength (N)	1112
Minimum Loop Tensile Strength (lb)	250
Maximum Operating Temperature (°C)	85
Maximum Operating Temperature (°F)	185
Minimum Operating Temperature (°C)	-60
Minimum Operating Temperature (°F)	-76
Minimum Installation Temperature (°C)	-20
Minimum Installation Temperature (°F)	-4
Standards Met	UL 62275 Compliant (Type 1, 11), UL Recognized (File #E56854), CSA Certified, RoHS Compliant
For Use With	GS4EH-E, ST3EH

Specifications (continued)

Part Features	One piece construction provides consistent, reliable performance. Low thread force. Used for heavy duty applications.
---------------	--

Packaging Detail

UPC	07498354230
Std. Pkg. Qty.	25
Std. Pkg. Volume (cf)	0.1453
Std. Ctn. Qty.	250
Std. Ctn. Volume (cf)	1.4527