



FEATURED

P1™ S100X150VAC Self-Lam Cassette, Vinyl, Wh, 200 Lbls, 1.5"x1", 0.5" PO H, PK1 S100X150VAC

The S100X150VAC Thermal Transfer Self-Laminating Label includes a white print-on area and clear overlamine to protect the legend for easy identification. It is sized specifically for wire and cable applications. The cassette contains an integrated memory device for automatic formatting, recall of last legend used, and the number of labels remaining. For use with LS8E and LS8EQ printers. Vinyl. 1.0" x 1.50" (25.4 mm x 38.1 mm). Color Clear/White. 200 labels/cassette. 1 cassette/package.

Specifications

Note	For use with LS8E and LS8EQ printers
Label Dimensions (In.)	1W x 1.5H
Product Type	Self-Laminating Label Cassette
Sub Brand	P1™
Color	White
Compatible Wire Gauge (AWG)	CAT. 5E/CAT. 6, 10 – 6 AWG
Material	Vinyl
Number of Labels per Cassette	200
Standards Met	RoHS Compliant
Maximum Cable Diameter (In.)	0.32
Maximum Cable Diameter (mm)	8.1
Minimum Cable Diameter (In.)	0.16
Minimum Cable Diameter (mm)	4
Label Width (In.)	1
Label Width (mm)	25.4
Label Height (In.)	1.5
Label Height (mm)	38.1
Print-On Area Height (In.)	0.5
Print-On Area Height (mm)	12.7
Minimum Operating Temperature (°C)	-46
Minimum Operating Temperature (°F)	-50
Maximum Operating Temperature (°C)	107
Maximum Operating Temperature (°F)	225
Part Features	Fast loading label cassette includes both label material and ribbon to make changing labels easy

Packaging Detail

UPC	07498335303
Std. Pkg. Qty.	1
Std. Pkg. Volume (cf)	0.0878
Std. Ctn. Qty.	10
Std. Ctn. Volume (cf)	0.8778