Product Data Sheet



Part Number: TRAUWT150-100 Last updated: August 2022

Page 1/2

Tape Underground Warning Electrical 100m Red 150mm Wide

Item Code: 3017204

Part Number: TRAUWT150-100

Underground warning tape should be buried halfway between the underground service and the surface of the earth. It provides a visual warning for any future excavation of the conduit, pipe, cable, or other service below. Trademate underground warning tapes are made of ultra-strong, pure grade polyethylene with lead-free pigments to prevent discolouration. They are highly tolerant to a wide range of soil pH.



General

Unit of Measure	Roll
Material	Polyethylene
Colour	Red
Dimensions	
Length	100 m
Width	150 mm
Operating Specifications	
Melting Temperature	125 °C
Tensile Strength	MD: 8.7 MPa, TD: 9.6 MPa



Elongation at Break	MD: 626%, TD: 887%
Dart Impact Strength	350 g
Tear Strength	MD: 5.2N, TD: 17.0N
Compliance	
Test Method	ISO 311357/03, ASTM D882, ASTM D1709, ASTM D1922
Standard	AS/NZS 2648.1:1995, AS/NZS 4275.1, AS/NZS 4275.2, AS/NZS 4275.3, AS/NZS 4275.4, AS/ NZS 4275.5

