

Product No: CRM-2T

ELKO DELAY ON TIMER Y-Î” 2C/O 16A 12-240V AC/DC CRM-2T



| General Information                |                                                                               |
|------------------------------------|-------------------------------------------------------------------------------|
| Brand                              | ELKO                                                                          |
| Product Type                       | Time Relay                                                                    |
| Technical Attributes               |                                                                               |
| Contacts                           | 2CO                                                                           |
| Function                           | Time 1 (Star): 0.1 Second to 100 Days, Time 2 (Delay): 0.1 Second to 1 Second |
| Rated Current (A)                  | 16                                                                            |
| Rated Frequency (Hz)               | 50/60                                                                         |
| Timing Range                       | 0.1s - 100 days                                                               |
| Universal Supply Voltage AC/DC (V) | 12-240                                                                        |
| Physical Attributes                |                                                                               |
| LED Colour                         | Supply - Green, Output - Red                                                  |
| Mounting Type                      | DIN Rail                                                                      |
| No. of Modules - Width 17.5 mm     | 1                                                                             |
| Operational Temperature Range (°C) | -20 to +55                                                                    |
| Storage Temperature (°C)           | -30 to +70                                                                    |
| Dimensions                         |                                                                               |
| Dimensions (mm)                    | 90 x 17.6 x 64                                                                |



Protection & Standards

|                         |                                      |
|-------------------------|--------------------------------------|
| Degree of Protection    | IP40 (Front Panel), IP20 (Terminals) |
| Pollution Degree        | 2                                    |
| Standards and Approvals | EN 61812-1                           |

Resources

|                              |                                    |
|------------------------------|------------------------------------|
| Product catalogue (Flipbook) | <a href="#">Download from here</a> |
|------------------------------|------------------------------------|