



HENSEL IP65 Outdoor Loadcentres



Pole

Configuration: 3 - 54 Poles.

Includes:

DIN rail, top hat profile 35mm.
Cable Entry Cover.
Pre-moulded Metric knockout cable entries.

Earth &

Neutral Bars:

FIXCONNECT® terminal technology.
Spring terminals for conductors up to 4mm².
Screw terminals for conductors up to 25mm².
Removable links for multiple protected neutral sections.

Degree of protection:

IP65.
Suitable for protected outdoor installation applications that is not in direct sunlight and indoor.
Resistant high pressure cleaning.
Water pressure: max 65 bar
water temperature max 50 °C.

Insulation voltage:

AC 400 V / DC 1000 V

Material:

Polystyrene/Polycarbonate halogen-free to IEC 754-2, silicon-free

Colour:

RAL7035 (Grey).

Glow wire test:

to IEC 60 695-2-11 750°C.

Temperature resistance:

-40 to +70°C.

Impact resistance:

Mechanical resistance IK 08 (5 Jaules).



Total Poles	Configuration	Dimensions			Part No.
		H	W	D	
3	1 Row	197	102	92	KV7103
4	1 Row	228	126	111	KV7104
6	1 Row	238	146	111	KV7106
9	1 Row	238	200	111	KV7109
12	1 Row	333	295	129	KV9112M
18	1 Row	333	403	129	KV9118M
24	2 Rows of 12P	458	295	129	KV9224M
36	2 Rows of 18P	483	403	129	KV9236M
36	3 Rows of 12P	583	295	129	KV9336M
48	4 Rows of 12P	708	295	129	KV9448M
54	3 Rows of 18P	630	403	129	KV9354M