

Horizon T Series

Residential metering enclosures for TAS applications



- Designed for both single and multi-phase installations.
- Provide safety, quality and performance.
- Suitable for domestic and light commercial metering applications.
- Easy-to-use gravity catch
- Ratchet sliding cable entry
- RotaDIN rotating / removable DIN section.
- Cord retainer for easy retention of extension cords.
- Identification with covered labelling section.
- Weatherproof installation label for AS/NZS3000 compliance.
- Padlockable facility.
- External frame mounting brackets.
- Meter lock-off device.
- Manufactured from 1.0 galvanised steel to Z275 or 316 stainless steel.
- Powdercoated Light Grey RAL7035 or N4.



ORDERING GUIDE

Part Number	DIN Space	Inclusions		Dimensions (mm)			Panel (mm)		
		RCCB Link [#]	63A MCB	Height	Width	Depth	Height	Width	Depth Behind
T11 ^{*†}				430	485	278	350	365	75
T20	24-pole	•	Segregated & lockable	688	485	278	350	365	75
T20/S	24-pole	•	Segregated & lockable	688	485	278	350	365	75

* For remote load centre applications

[#] RCCB Links provide RCD expansion to 3 circuits

[†] While stocks last

ORDERING GUIDE – COMBINED SERVICES

Part Number	Enclosures		Inclusions				Dimensions (mm)			Panel (mm)		
	T20	HZN/COM1 [^]	DIN	Earth bar	Neutral bar	63A MCB	Height	Width	Depth	Height	Width	Depth Behind
T82	•	•	24-pole	•	•	Segregated & lockable	1120	485	278	350	365	75

[^]For more information on HZN/COM1 enclosures please refer to page 12.

ACCESSORIES

Part Number	Product	Description	T11	T20	T20/S	T82
HZN/T10P3KIT	3Ø upgrade kit	Includes 2 x additional MCB lock-off devices		•	•	•
HZN/FK8	Flush kit	For flush mounting		•	•	
HZN/FK13 [†]						•
HZN/JK2 [†]	Bolt kit	For combining with a HZN/COM [^] enclosure	•	•	•	

[†] While stocks last

[^] For more information on the HZN/COM enclosure range please refer to page 12.