



AMP-TWIST SL-Series Modular Jack, category 6A, shielded, 4 pair, for F/UTP cables, side exit, without dust cover

OBSOLETE

This product was discontinued on: September 29, 2020

Replaced By:

2153449-4 AMP-TWIST SLX Series Modular Jack, category 6A, shielded , 4 Pair, without dust cover, gray

760245049 4D-CAP-SLX-50 Four-Direction Cable Exit Cap for SLX Jacks, bag of 50 pcs

Product Classification

Regional Availability	Australia/New Zealand EMEA Latin America
Portfolio	NETCONNECT®
Product Type	Modular jack
Product Series	SL Series

General Specifications

ANSI/TIA Category	6A
Cable Type	Shielded
Color	Silver
Conductor Type	Solid Stranded
Integrated Dust Cover Type	None
Outlet Type	Standard
Termination Tool	SL Termination tool
Termination Type	IDC
Transmission Standards	ANSI/TIA-568-C.2 ISO/IEC 11801 Class EA
Wiring	T568A T568B

1711343-2

Dimensions

Panel Cutout, recommended	14.78 x 20.07 mm (0.58 x 0.79 in)
Panel Thickness, recommended	1.6 mm 0.063 in
Height	20.5 mm 0.807 in
Width	21.5 mm 0.846 in
Depth	36.7 mm 1.445 in
Compatible Cable Diameter, maximum	9 mm 0.354 in
Compatible Insulated Conductor Diameter, maximum	1.6 mm 0.063 in
Contact Plating Thickness	1.27 µm
Compatible Conductor Gauge, solid	24–22 AWG
Compatible Conductor Gauge, stranded	26–24 AWG

Material Specifications

Contact Base Material	Beryllium copper
Contact Plating Material	Gold
Material Type	Zinc alloy

Environmental Specifications

Flammability Rating	UL 94 V-0
----------------------------	-----------

Packaging and Weights

Packaging quantity	12
Packaging Type	Tray in box

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant

