



AMBOS

ELECTRICAL & SAFETY

POINT OF ATTACHMENT BRACKETS & ACCESSORIES

P: 02 9522 7800 F: 02 9522 7900

E: sales@clarkeind.com.au

NSW Approved Tubular Point of Attachment Brackets

'B' RATED SINGLE LEG BRACKETS

Suitable for single or three phase aluminium aerial service lines up to approx. 30m in length.

For exact details regarding required bracket strength ratings for particular applications, please refer to the New South Wales Service & Installation Rules, your local Supply Authority or Service Provider.

'SR' style brackets can have a tendency to twist when subject to sideways service line tension. For applications where the service line will be pulling on the bracket at an angle greater than 45° it is recommended that a "D" rated double leg bracket is used to avoid twisting the bracket mounting.



CAT No.	NOMINAL HEIGHT	APPLICATION
---------	----------------	-------------

AMRB2B1/SR	300mm	Single Rafter. Rafter Mount with riser in front of gutter. Designed to simplify mounting this bracket installs via 40 dia hole through Fascia under Quad style gutter or similar. No penetration of roofing material or flashing of bracket required. 2 x M10 Bolts supplied for fixing, plus 2 x T17 Tek screws.
AMRB3B1/SR	450mm	
AMRB4B1/SR	600mm	

AMRB3B1/LH	450mm	Side Mount. For fixing to rafter and penetrating through roofing material or fixing to side fascia or verandah beam. 'S' shaped tubular design allows for consumer mains to be run through centre of bracket for a neater installation and to simplify flashing of bracket where required. Available in left and right hand. Left hand bracket shown. 3 x M12 galvanised bolts required for fixing (not supplied).
AMRB3B1/RH	450mm	
AMRB4B1/LH	600mm	
AMRB4B1/RH	600mm	
AMRB5B1/LH	750mm	
AMRB5B1/RH	750mm	
AMRB6B1/LH	900mm	
AMRB6B1/RH	900mm	

P: 02 9522 7800 F: 02 9522 7900

E: sales@clarkeind.com.au

NSW Approved Tubular Point of Attachment Brackets

'B' RATED SINGLE LEG BRACKETS

Suitable for single or three phase aluminium aerial service lines up to approx. 30m in length.

For exact details regarding required bracket strength ratings for particular applications, please refer to the New South Wales Service & Installation Rules, your local Supply Authority or Service Provider.

For applications where the service line will be pulling on the bracket at an angle greater than 45° it is recommended that a "D" rated double leg bracket is used to avoid twisting the bracket mounting.



CAT No.	NOMINAL HEIGHT	APPLICATION
---------	----------------	-------------

AMRB3B1/SFG	450mm	Fascia Mount. For fixing to fascia under gutter. Must be bolted to hardwood noggin of adequate strength fixed between rafters directly behind fascia board or using Clarke fascia support bracket (Part no. CI SB1/LH or /RH) M12 galvanised bolts required for fixing (not supplied). 'S' shaped tubular design allows for consumer mains to be run through centre of bracket for a neater installation
AMRB4B1/SFG	600mm	
AMRB5B1/SFG	750mm	
AMRB6B1/SFG	900mm	

AMRB3B1/RF	450mm	Rafter / Fascia Mount. For fixing to fascia under gutter with the added strength of rafter support bar. Our strongest mounting single leg bracket, this bracket provides greater resistance to twisting when the angle of service line pull exceeds 45°. M12 galvanised bolts required for fixing (not supplied). 'S' shaped tubular design allows for consumer mains to be run through centre of bracket for a neater installation.
AMRB4B1/RF	600mm	
AMRB5B1/RF	750mm	
AMRB6B1/RF	900mm	

P: 02 9522 7800 F: 02 9522 7900

E: sales@clarkeind.com.au

NSW Approved Tubular Point of Attachment Brackets

'D' RATED DOUBLE LEG BRACKETS

Suitable for single or three phase aluminium aerial service lines up to approx. 50m in length or for any service line pulling on the bracket at an angle greater than 45° to the perpendicular.

For exact details regarding required bracket strength ratings for particular applications, please refer to the New South Wales Service & Installation Rules, your local Supply Authority or Service Provider.

CAT No.	NOMINAL HEIGHT	APPLICATION
---------	----------------	-------------

AMRB2D1/45	300 x 450mm	Double Leg Rafter. Rafter Mount with riser in front of gutter. Designed to simplify mounting this bracket installs via 2 x 40 dia holes through Fascia under Quad style gutter or similar. No penetration of roofing material or flashing of bracket required. Not suitable for full depth fascia gutters. For this application use Clarke style double leg rafter bracket which mounts behind fascia and penetrates through roofing material. Available in two widths to suit 450mm or 600mm nominal rafter spacing. Bracket legs will flex to take up minor discrepancies in rafter spacing without compromising strength. 4 x M10 Bolts supplied for fixing.
AMRB3D1/45	450 x 450mm	
AMRB4D1/45	600 x 450mm	
AMRB5D1/45	750 x 450mm	
AMRB6D1/45	900 x 450mm	
AMRB2D1/60	300 x 600mm	
AMRB3D1/60	450 x 600mm	
AMRB4D1/60	600 x 600mm	
AMRB5D1/60	750 x 600mm	
AMRB6D1/60	900 x 600mm	



P: 02 9522 7800 F: 02 9522 7900
E: sales@clarkeind.com.au