

COMMUNICATION CABLES – Telephone Cables

TELEPHONE LEAD IN U/G M@XTEL®



Cable description:

Lead In Cables - Underground.

Solid PACW, Solid PE Insulated, PE Sheathed. Available with an optional Nylon Termite Resistant Jacket. ACMA Approved.



Telstra serial/item number	Prysmian material code	Material description	No. of pairs	kg/km	Min. bending radius mm	Overall diameter mm	Standard pack length mm	Stock/ MTO	Nominal drum dimensions mm	Max hauling tension N
490/05023	5414776	CABLE, TEL LEAD-IN 2/0.40 PEIFLI PE	2	18.5	80	4.6	500	Stock	REELEX - 415/415/225 (MAGENTA)	50
490/08123	5432879	CABLE, TEL LEAD-IN 2/0.40 PEIFLI PEHJC	2	20	100	4.7	500	Stock	1xREEL (338/102/230), CRTN (340/340/245)	50
490/05741	5414790	CABLE, TEL LEAD-IN 2/0.64 PEILI PEIB	2	38	100	4.4	500	Stock	1xREEL (338/102/230), CRTN (340/340/245)	1000
490/08142	5432886	CABLE, TEL LEAD-IN 2/0.64MM CPFLLI PEHJC	2	37	100	6.3	500	Stock	1xREEL (422/102/306), CRTN (435/435/320)	120
490/05024	5407211	CABLE, TEL LEAD-IN 5/0.40 PEIFLI PE	5	29	100	5.2	500	Stock	REELEX - 415/415/225 (MAGENTA)	120
490/08124	5432916	CABLE, TEL LEAD-IN 5/0.40 PEIFLI PEHJC	5	34	100	5.8	500	Stock	1xREEL (422/102/306), CRTN (435/435/320)	120

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group; any modification or alteration afterwards of product may give different result. The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.

Prysmian Cables & Systems Australia Pty Ltd

1 Heathcote Road, Liverpool 2170 NSW, Australia
 Ph: 1300 300 304 Fx: 1300 300 307
 E-mail: sales.au@prysmiangroup.com

www.prysmiancable.com.au

