

FLASHING AND STATIC BEACONS

Microlamp L MT



- Multi voltage (12 - 48Vdc or 24 - 240Vac)
- Optional mounting base
- Double insulated
- Continuous or flashing
- Available with LED bulbs

SPECIFICATIONS

VOLTAGE	CURRENT	LUMINOUS INTENSITY
12V	420mA	25Cd(p)
24V	215mA	18Cd(p)
48V	105mA	8Cd(p)
110V	45mA	3Cd(p)
240V	20mA	2Cd(p)

Voltage Range:	12 to 48Vdc or 24 to 240Vac ± 10% 50/60Hz
Bulb:	BA15D 5W (LED types LD103, LD105, LAD143F, LD145F)
Flash Rate:	110fpm ±20
Protection:	IP54
Temp Rating (°C):	-30 to +50
Cable Entry:	Through Base
Construction:	Polycarbonate Base and Dome
Weight:	0.12Kg

ORDER CODES

Note: bulb must be ordered separately to suit operating voltage

SIR1504840*	12-48Vdc
SIR1524040*	24-240Vac

****SPECIFY COLOUR A = Amber, B = Blue, C = Clear, G = Green, R = Red**

BULBS

SIR3906012	BA15D 5W 12V
SIR3906024	BA15D 5W 24V
SIR3906048	BA15D 5W 48V
SIR3906110	BA15D 5W 110V
SIR3906240	BA15D 5W 240V

ACCESSORIES AND SPARE PARTS

SIR3500001*	Microlamp Dome (**Specify Colour)
SIR3815001	Microlamp P single bolt base
SIR3815002	Microlamp E27 base

