

LED BEACONS

B400LDA



- Multi-function LED beacon
- 9 flash patterns
- Externally selectable 2nd stage
- Wide Voltage ranges
- Wall mount and tube mount accessories

SPECIFICATIONS

VOLTAGE	CURRENT
10-50Vac/dc	400mA
115Vac	140mA
240Vac	70mA

FLASH PATTERNS

Stage 1	Stage 2
Static	Alternate side flash 2Hz
Rotating Fast 1	Single Flash 2Hz
Rotating Fast 2	Double Flash 2Hz
Rotating Slow 1	Alternate side flash 2Hz
Rotating Slow 1	Double Flash 1 Hz
Double Flash 1 Hz	Alternate side flash 2Hz
Single Flash 2Hz	Rotating Fast 2
Double Flash 2Hz	Rotating Fast 2
Alternate side flash 2Hz	Rotating Fast 2

Flash Rate:	See table
Lamp:	32 x LED array
LED Life:	50,000 hours
Voltage Tolerance:	±5% (ac 50/60Hz)
Protection:	IP65
Temp Rating (°C):	-25 to +50
Cable Entry:	Through base (8mm)
Construction:	Polycarbonate
Weight:	0.85Kg
Mounting:	Horizontal or Vertical

ORDER CODE

ESSB400LDA050B*	10-50Vdc
ESSB400LDA115B*	115Vac
ESSB400LDA230B*	240Vac

***SPECIFY COLOUR A = Amber, B = Blue, G = Green, R = Red, Y=Yellow**

ACCESSORIES AND SPARE PARTS:

ESS9B400S*	B400LDA Dome (*Specify colour)
ESSB400RAB001	B400 wall mount bracket
ESSB400TMA001	B400 tube mount (145mm high)

