

BELLS

Mechtric Solenoid Bells



- Robust bell for fire and industrial applications
- 3 sizes
- 6 and 8 inch model suitable for outdoor use with optional back box
- Available in red or grey

SPECIFICATIONS

VOLTAGE	CURRENT	SOUND LEVEL	CURRENT	SOUND LEVEL	CURRENT	SOUND LEVEL
100mm			150mm		200mm	
12Vdc	180mA	83dB	100mA	86dB	140mA	85dB
24Vdc	90mA	83dB	50mA	90dB	70mA	92dB
240Vac	35mA	83dB	40mA	90dB	60mA	88dB

Sound Frequency:	2000 – 12,000 Hz
Rating:	1 Hour
Protection:	IP20 IP55 with back box
Temp Rating (°C):	-35 to +70
Cable Entry:	Side or Back
Construction:	Steel Gong, Aluminium Body
Weight:	0.4Kg (MB100) 1.0Kg (MB150) 1.75Kg (MB200)

ORDER CODE

100mm	150mm	200mm	
MB100012D*	MB150012D*	MB200012D*	12Vdc
MB100024D*	MB150024D*	MB200024D*	24Vdc
MB100240A*	MB150240A*	MB200240A*	240Vac

****SPECIFY COLOUR: R = Red, G = Grey**

ACCESSORIES AND SPARE PARTS

MBBOX* Back Box (100mm x 100mm)

****SPECIFY COLOUR: R = Red, G = Grey**

