

Catalogue No: **3PS6G**

3PS63 HANDLE SUITS CABLE DIA 9-29mm

Plugs, Sockets and Switches > Isolating Plugs and Sockets > Isolating Plugs and Sockets > Proconnect Plugs and Sockets > 90A Deconnector Plugs and Sockets (3PS63 Series) > Accessories



3Ps63 Handle Suits Cable Diam 9-29Mm



Representative Photo Only
(actual product may vary based on configuration selections)

- Available in five sizes including 30A, 50A, 90A, 150A and 250A (Maximum current rating to IEC60309)
- 3, 4 and 5 pin configurations with optional pilot pins, silver alloy tipped for low voltage drop and high arc resistance
- AC23 rating for making and breaking high inductive loads
- Connect and disconnect under load, eliminates the need for switching
- Interlocked socket and appliance inlet with 24 insert settings (Factory Set) preventing mismatching for a safe and reliable connection
- High ingress protection and exceptional impact resistance, IP66 / IK 08
- Resistance to most industrial chemicals, detergents and exposure to UV light
- Range of angled wall boxes, incline sleeves and handles for all plug and socket combinations

SPECIFICATIONS

| | |
|----------------------------------|--|
| Product Series | 3PS |
| Component Type Plugs And Sockets | Accessory |
| Diameter, Cable Jacket, Min | 9 mm |
| Diameter, Cable Jacket, Max | 29 mm |
| Standards Compliance | AS/NZS 3947.3 IEC 60309-1 IEC 60529 IEC 60947-3 |

REFERENCES

| | |
|---|---|
| IECEX Certificate | - |
| Supplier Declaration of Conformity: | - |
| Installation Guide: | - |
| User Manual: | - |
| Manufacturer Datasheet: | - |
| Manufacturer Catalogue & Product Selection: | - |