Catalogue No: **3PS9PC**

3PS125 APPLIANCE INLET PLUG CAP

Plugs, Sockets and Switches > Isolating Plugs and Sockets > Isolating Plugs and Sockets > Proconect Plugs and Sockets > 150A Deconnector Plugs and Sockets (3PS125 Series) > Accessories





3Ps125 Appliance Inlet Plug Cap

- Available in five sizes including 30A, 50A, 90A, 150A and 250A (Maximum current rating to IEC60309)
- 3, 4 and 5 pin configurations with optional pilot pins, silver alloy tipped for low voltage drop and high arc resistance
- AC23 rating for making and breaking high inductive loads
- Connect and disconnect under load, eliminates the need for switching
- Interlocked socket and appliance inlet with 24 insert settings (Factory Set) preventing mismating for a safe and reliable connection
- High ingress protection and exceptional impact resistance, IP66 / IK 08
- Resistance to most industrial chemicals, detergents and exposure to UV light
- Range of angled wall boxes, incline sleeves and handles for all plug and socket combinations

Representative Photo Only (actual product may vary based on configuration selections)

SPECIFICATIONS		
Product Series		3PS
Component Type Plugs And Sockets		Accessory
Standards Compliance		AS/NZS 3947.3 IEC 60309-1 IEC 60529 IEC 60947-3
REFERENCES		
IECEx Certificate	-	
Supplier Declaration of Conformity:	-	
Installation Guide:	-	
User Manual:	-	
Manufacturer Datasheet:	-	
Manufacturer Catalogue & Product Selection:	-	

