

# Product Characteristics

**Part Number: CBL1.04CODFXBK**

CABLE FLEX ORDINARY DUTY 1.0MM 32/020 4C 100M BLACK SHEATH

## Description:



Flexible cable comprises of multiple individually insulated cables contained in a round outer sheath. Used where flexibility is required such as power supply leads for moveable equipment or controls. Typically is also used in domestic and industrial extension leads. Suitable for glanding.

| Attribute Name                           | Attribute Value    |
|--|--------------------|
| Core insulation                          | PVC                |
| Nominal voltage U                        | 0.25 kV            |
| Nominal cross section conductor          | 1 mm <sup>2</sup>  |
| Colour outer sheath                      | Black              |
| Conductor material                       | Copper             |
| With earthing                            | Yes                |
| Number of cores                          | 4                  |
| Inner conductor category                 | Class 5 = flexible |
| Nominal voltage U0                       | 0.44 kV            |
| Conductor category                       | Class 5 = Flexible |
| Material outer sheath                    | PVC                |
| Core identification                      | Colour             |
| Permitted cable outer temperature, fixed | 90 °C              |
| Class                                    | Ordinary duty      |

| Classifications |          |
|-----------------|----------|
| ETIM            | EC000057 |
| UNSPSC          | 26121629 |

Create Date:

## Disclaimer

*For use on datasheets that are created by Rexel*

The information in this document is intended to provide a brief summary of our knowledge of this product. It has been compiled from sources we believed at the time of compilation to be reliable and accurate. It is not meant to be an exhaustive and complete document about the product. Rexel does not warrant that it is accurate, complete or up to date.

Each user of this information needs to verify (including by its own risk analysis, evaluation and testing) the product's characteristics and features in light of its particular intended use for the product. Each user should, before purchasing this product and before use, obtain the latest relevant information from the manufacturer, details of which can be provided by the Rexel Australia group.

The Rexel Australia group excludes all warranties or guarantees implied by law, and all liability for any error, inaccuracy, loss or damage resulting from the use of this information. No rights to reproduce this document are granted by the publication of this document. This publication may be changed at any time.