



Shaft 320mm length suits to SLB 125-630A with S2 handles



- Double break per pole offers high durability and short-circuit withstand
- Use of glass fibre reinforced polyester provides high mechanical and thermal resistance (does not include SLBM or VLBM modular series)
- Quick and easy to install thanks to good centre to centre distance and connection accessories including copper connecting links.
- Wide range of accessories available which is flexible in adapting to various applications and reduces the cost of management and storage
- All Socomec load break switches are compatible with the ergonomic IP65 S-Type Handles which features interlocking (in the ON position), padlocking, UV and chemical agent resistive material and the choice of standard blue or red / yellow colour

Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

| | |
|--|----------------|
| Component Type Power Distribution & Protection | Shaft |
| Details, Switch | VLB 250...500A |
| Distance, Backplate to Door, Min | 95 mm |
| Distance, Backplate to Door, Max | 350 mm |
| Width, Shaft | 10 mm |
| Length, Shaft | 350 mm |
| Shape, Shaft Cross Section | Square shaft |

REFERENCES

| | |
|---|---|
| IECEX Certificate | - |
| Supplier Declaration of Conformity: | - |
| Installation Guide: | - |
| User Manual: | - |
| Manufacturer Datasheet: | - |
| Manufacturer Catalogue & Product Selection: | 14001032_Manufacturer Product Selection Guide |