

**HANDLE T S4 I-O**

- Double break per pole offers high durability and short-circuit withstand
- Use of glass fibre reinforced polyester provides high mechanical and thermal resistance (does not include SLBM or VLBM modular series)
- Quick and easy to install thanks to good centre to centre distance and connection accessories including copper connecting links.
- Wide range of accessories available which is flexible in adapting to various applications and reduces the cost of management and storage
- All Socomec load break switches are compatible with the ergonomic IP65 S-Type Handles which features interlocking (in the ON position), padlocking, UV and chemical agent resistive material and the choice of standard blue or red / yellow colour

Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

Component Type Power Distribution & Protection	Handle
Number of Poles	4
Details, Switch	SLB 800...1800A
Handle Type	S4 T Handle type
Colour, Handle	Blue & Black colour
Details, text	"OFF" padlockable, "ON" locking field convertible. Front operation, T-type S4 handle.
IP Rating	IP65
Padlockable	Yes

REFERENCES

IECEx Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	14433111_Manufacturer Product Selection Guide


Catalogue No: **14433111**

HANDLE EXTERNAL MOUNT S4 TYPE IP65 BLACK


Power Distribution and Protection > Isolators and Transfer Switches > Load Break Switches > Socomec Load Break Switches > Socomec Accessories for Load Break Switches > External Mount Handle - S Type Series



Direct operation



Connection terminals



- ① Direct operation
- ② S type auxiliary contact N/O + N/C
- ③ Rear connection (option)
- ④ 1 to 8 pre-break auxiliary contact for signalling
- ⑤ Terminal shrouds

Dimension Diagram