



Representative Photo Only  
(actual product may vary based on configuration selections)

**AUX CONTACT 1NO+1NC SIRCO M**

- Double break per pole offers high durability and short-circuit withstand
- Use of glass fibre reinforced polyester provides high mechanical and thermal resistance (does not include SLBM or VLBM modular series)
- Quick and easy to install thanks to good centre to centre distance and connection accessories including copper connecting links.
- Wide range of accessories available which is flexible in adapting to various applications and reduces the cost of management and storage
- All Socomec load break switches are compatible with the ergonomic IP65 S-Type Handles which features interlocking (in the ON position), padlocking, UV and chemical agent resistive material and the choice of standard blue or red / yellow colour

**SPECIFICATIONS**

|  |                   |
|--|-------------------|
| Component Type Power Distribution & Protection | Auxiliary Contact |
| Number of Poles                                | 3                 |
| Details, Switch                                | SLBM 16...125A    |
| Contact Configuration                          | 1 NO + 1 NC EB    |
| Ie, Rated Operational Current, nom             | 10 A,nom          |
| Ie, Rated Operational Current, nom             | 10 A,nom          |

**REFERENCES**

|   |   |
|---|---|
| IECEX Certificate                           | -   |
| Supplier Declaration of Conformity:         | -   |
| Installation Guide:                         | -   |
| User Manual:                                | -   |
| Manufacturer Datasheet:                     | -   |
| Manufacturer Catalogue & Product Selection: | <a href="#">22990001_Manufacturer Product Selection Guide</a> |