



SHROUD 3/4P VLB160-200



- Double break per pole offers high durability and short-circuit withstand
- Use of glass fibre reinforced polyester provides high mechanical and thermal resistance (does not include SLBM or VLBM modular series)
- Quick and easy to install thanks to good centre to centre distance and connection accessories including copper connecting links.
- Wide range of accessories available which is flexible in adapting to various applications and reduces the cost of management and storage
- All Socomec load break switches are compatible with the ergonomic IP65 S-Type Handles which features interlocking (in the ON position), padlocking, UV and chemical agent resistive material and the choice of standard blue or red / yellow colour

Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

| | |
|--|--|
| Component Type Power Distribution & Protection | Terminal Cover |
| Number of Poles | 3 |
| Package Quantity | 1 qty |
| Details, Switch | VLB 160...200A |
| Details, text | Top and bottom mounting position. 2 set required, 1 for line and 1 for load. |
| Mounting Position | Top / Bottom |
| IP Rating | IP20 |

REFERENCES

| | |
|---|---|
| IECEX Certificate | - |
| Supplier Declaration of Conformity: | - |
| Installation Guide: | - |
| User Manual: | - |
| Manufacturer Datasheet: | - |
| Manufacturer Catalogue & Product Selection: | 25944020_Manufacturer Product Selection Guide |