

## ELB-P Enclosed load-break switches COMO M Enclosed 20 to 100 A

New Range

The IP 65 range of enclosed switches from Socomec, not only come fitted standard with a fully capable COMO M switch, they are also provided with a neutral and earth terminal for easy connection.

Due to its spacious design, the COMO M enclosed switch allows for the fitting of two additional modules, one on each side, increasing the functionality of the switch.

With standard knockouts in all enclosures between 20 and 63 A as well as the prominent red handle and yellow cover, The COMO M enclosed range offers a solution for any enclosed load-break requirements.



### ELB-P Insulated enclosed type load-break switch


Switch (A)	AC 22 400 V (A)	AC 23 400 V (A)	AC 23 400 V (kW)	Enclosure dimensions (mm) H x W x D	Cat. No.
SLB 20 3P	20	20	9		ELB-P 20 3P
SLB 25 3P	25	25	11		ELB-P 25 3P
SLB 32 3P	32	32	15		ELB-P 32 3P
SLB 40 3P	40	40	18.5		ELB-P 40 3P
SLB 63 3P	63	63	30		ELB-P 63 3P
SLB 80 3P	80	80	40		ELB-P 80 3P
SLB 100 3P	100	80	40		ELB-P 100 3P

**Note:** For switch accessories refer SLB accessories.


**Housing material:** Polycarbonate  
**Housing colour:** Grey casing, red/yellow handle  
**Degree of protection:** IP 65  
**Entries:** metric knockouts

### Dimensions


ELB 20 to 32 A



ELB 40 to 63 A



ELB 80 to 100 A







# ELB-S Enclosed load-break switches


## IP 65 Steel enclosed 20 to 1600 A

**New Range**

- Superior switching capabilities
- Most types ex-stock for immediate delivery
- Custom built switches available at short lead time
- All enclosures IP 65 rated
- Rating from 20 A to 1600 A
- Customised lock fitted, other locking option available
- Door hinged left or right

### ELB-S Steel enclosed type load-break switch

Switch (A)	Enclosure type	Enclosure dimensions (mm)			Cat. No.
		Height	Width	Depth	
SLB 20 3P					ELB-S 20 3P
SLB 25 3P					ELB-S 25 3P
SLB 32 3P	MAS0202015	200	200	155	ELB-S 32 3P
SLB 40 3P					ELB-S 40 3P
SLB 63 3P					ELB-S 63 3P
SLB 80 3P	MAS0202515	300	250	155	ELB-S 80 3P
SLB 100 3P					ELB-S 100 3P
SLB 125 3P	MAS0352515	350	250	155	ELB-S 125 3P
SLB 160 3P					ELB-S 160 3P
SLB 200 3P	MAS0403021	400	300	210	ELB-S 200 3P
SLB 250 3P					ELB-S 250 3P
SLB 315 3P	MAS0503021	500	300	210	ELB-S 315 3P
SLB 400 3P					ELB-S 400 3P
SLB 500 3P	MAS0604021	600	400	210	ELB-S 500 3P
SLB 630 3P					ELB-S 630 3P
SLB 800 3P					 ELB-S 800 3P
SLB 1000 3P	MAS0705026	700	500	260	 ELB-S 1000 3P
SLB 1250 3P					 ELB-S 1250 3P
SLB 1600 3P					 ELB-S 1600 3P

**Notes:** Custom size enclosures available. Refer NHP. For switch accessories refer SLB accessories.  
 This product is manufactured to order at a short lead time.

**Housing material:**

Steel plate 1.2/1.5 mm

**Housing colour:**

Grey RAL 7032

**Degree of protection:**

IP 65

