Horizon N Series

Residential metering enclosures for NSW applications















- Designed for both single and multi-phase installations.
- Provide safety, quality and performance.
- Suitable for domestic and light commercial metering applications.
- Easy-to-use gravity catch
- · Ratchet sliding cable entry
- RotaDIN rotating / removable DIN section.
- Cord retainer for easy retention of extension cords.
- Identification with covered labelling section.
- Weatherproof installation label for AS/NZS3000 compliance.
- Padlockable facility.
- External frame mounting brackets.
- Manufactured from 1.0 galvanised steel to Z275 or 316 stainless steel.
- Powdercoated Light Grey RAL7035 or N4.



ORDERING GUIDE - HORIZON N

		I	Dimensions (mm)			Panel (mm)			
Part Number	DIN space	RCCB Link#	Earth & Neutral Link	Height	Width	Depth	Height	Width	Depth Behind
A10^	24-pole	•	•	690	485	278	480	461	75
N20*	24-pole	•	•	690	485	278	480	461	75
N20/S	24-pole	•	•	690	485	278	480	461	75
N22*	48-pole	•	•	860	485	278	480	461	75

^{*} Comes with pre-drilled panel for single or 3Ø metering

[^] Actew AGL approved

ACCESSORIES					S)		
	Part Number	Description	A10	N20	N20/	N21	N22
	HZN/FK8	Flush kit	•	•	•	•	•
	HZN/JK2 [†]	Bolt kit for combining with a HZN/COM^ enclosure		•			
	HZN/GAS1	Standard gas meter	•	•	•	•	•

[†] While stocks last

[#] RCCB Links provides RCD expansion to 3 circuits

[^] For more information on the HZN/COM enclosure range please refer to pages 12.