



### Main

Range	Multi 9
Product or component type	OC contact
Device short name	OFSP
Signal contacts composition	1 C/O 1 NC
[Ie] rated operational current	3 A at 380...415 V AC - 50/60 Hz 6 A at 220...240 V AC - 50/60 Hz 1 A at 130 V DC 1.5 A at 60 V DC 2 A at 48 V DC 6 A at 24 V DC

### Complementary

Mounting mode	Fixed
Mounting support	DIN rail
Connections - terminals	Tunnel type terminal 2 cable(s) 1...1.5 mm <sup>2</sup> flexible Tunnel type terminal 2 cable(s) 1...1.5 mm <sup>2</sup> rigid
Tightening torque	0.8 N.m

### Environment

standards	EN/IEC 60947-5-1
IP degree of protection	IP20 conforming to EN/IEC 60947-5-1
pollution degree	3 conforming to EN/IEC 60947-5-1
ambient air temperature for operation	-25...50 °C
ambient air temperature for storage	-40...85 °C

### Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 0630 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product end of life instructions	Need no specific recycling operations