



Main

Range of product	Harmony XVS
Product or component type	Multisound siren
Device short name	XVS

Complementary

Colour	White
Material	PC (polycarbonate) (back cover) ASA (Acrylonitrile Styrene Acrylate) (front) ASA (Acrylonitrile Styrene Acrylate) (back)
Product weight	1 kg
Marking	CE
Mounting support	Bracket
Fixing mode	3 holes Ø 9 mm
[Uimp] rated impulse withstand voltage	0.8 kV
Current consumption	250 mA at 12 V 350 mA at 24 V
Electrical connection	Cable : 6.5...8.5 mm, 0.33 mm ² / AWG 22 (signalling circuit) Cable : 6.5...8.5 mm, 0.52 mm ² / AWG 20 (power circuit)
Width	140 mm
Height	114 mm
Depth	223 mm

Environment

signalling type	43 tones siren
standards	EN 55014-2 EN 55022 EN 61000-6-2 EN 61000-6-3
product certifications	UL
protective treatment	TC
ambient air temperature for storage	-35...70 °C
ambient air temperature for operation	-10...50 °C
overvoltage category	Class II conforming to EN/IEC 61140
IP degree of protection	IP53 conforming to EN/IEC 60529
[Us] rated supply voltage	12 V DC 24 V DC
noise level	0...105 dB (continuous or intermittent tone) at 1 m

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1611 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available

