XVS14MMW

multisound siren XVS - 43 tones - 0..105 dB - white - IP53





Main

Range of product	Harmony XVS
Product or component type	Multisound siren
Device short name	XVS

Complementary

Colour	White	
Material	PC (polycarbonate) (back cover) PC (polycarbonate)/ABS (acrylonitrile butadiene-styrene) (front) PC (polycarbonate)/ABS (acrylonitrile butadiene-styrene) (back)	
Product weight	1.2 kg	
Marking	CE	
Mounting support	Bracket	
Fixing mode	3 holes Ø 9 mm	
[Uimp] rated impulse withstand voltage	4 kV	
Current consumption	50 mA at 240 V	
Electrical connection	Cable: 6.58.5 mm, 0.33 mm ² / AWG 22 (signalling circuit) Cable: 6.58.5 mm, 0.52 mm ² / AWG 20 (power circuit)	
Width	140 mm	
Height	114 mm	
Depth	223 mm	

Environment

Liivii Oliiliciit		
signalling type	43 tones siren	
standards	EN 60947-5-1	
	EN 61000-6-2	
	EN 61000-6-3	
	EN 60947-01	
product certifications	UL	-
protective treatment	TC	
ambient air temperature for storage	-3570 °C	
ambient air temperature for operation	-1050 °C	
overvoltage category	Class II conforming to EN/IEC 61140	
IP degree of protection	IP53 conforming to EN/IEC 60529	
[Us] rated supply voltage	240 V AC	
noise level	0105 dB (continuous or intermittent tone) at 1 m	

Offer Sustainability

Sustainable offer status	Green Premium product	_
RoHS (date code: YYWW)	Compliant - since 1611 - Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
Product environmental profile	Available	

Siren

Dimensions







