


Black 2/1 thin wall heat-shrink tubing without glue 13/6.5 mm 4 ft



Characteristics

Colour : **Black**
Wall Ø before shrinking (mm) : **13**
Wall Ø after shrinking (mm) : **6.5**

GENERAL INFORMATION

Description

Thin wall 2/1 heat-shrink tubing without adhesive.

Technical details

Thin wall, 2/1 shrinkage in length 1.2 meter.
Heat-shrink tubing in flexible flame retardant polyolefin (except clear).
Working temperature: -45 °C to +125 °C (clear is -45 °C to +105 °C).
Shrink temperature: 120 °C (clear is 105 °C).
Dielectric strength (IEC 243): 15 kV/mm.
Tensile strength: 10.4 Mpa.
Rate voltage: 600 V.
Self-extinguishing in accordance with UL224 (except clear).

Application(s)

For general and specific applications in the following areas: electrical insulation, marking and identification, protection (mechanical against corrosion), management and maintenance of wires.

ADDITIONAL INFORMATION

Color and diameter next pages.

LOGISTIC INFORMATION

Packaging



No packaging

Height (cm) : 0.65
Length (cm) : 120
Depth (cm) : 2
Net weight (kg) : 0.02
Gross weight (kg) : 0.02



Outer package 1



Bag

Height (cm) : 9.8
Length (cm) : 120
Depth (cm) : 2
Net weight (kg) : 0.19
Gross weight (kg) : 0.21



x 10

Outer package 2



Carton box

Height (cm) : 16
Length (cm) : 130
Depth (cm) : 20
Net weight (kg) : 6.3
Gross weight (kg) : 6.8



x 250

Outer package 3



Pallet

Height (cm) : 115
Length (cm) : 130
Depth (cm) : 80
Net weight (kg) : 175
Gross weight (kg) : 189



x 7000