

# Blue 2/1 thin wall heat-shrink tubing without glue 2.5/1.3 mm 4 ft



## Characteristics

Colour : **Blue**  
 Wall Ø before shrinking (mm) : **2.5**  
 Wall Ø after shrinking (mm) : **1.3**

## GENERAL INFORMATION

### Description

Thin wall 2/1 heat-shrink tubing without adhesive.

### Technical details

Thin wall, 2/1 shrinkage in length 1.2 meter.  
 Heat-shrink tubing in flexible flame retardant polyolefin (except clear).  
 Working temperature: -45 °C to +125 °C (clear is -45 °C to +105 °C).  
 Shrink temperature: 120 °C (clear is 105 °C).  
 Dielectric strength (IEC 243): 15 kV/mm.  
 Tensile strength: 10.4 Mpa.  
 Rate voltage: 600 V.  
 Self-extinguishing in accordance with UL224 (except clear).

### Application(s)

For general and specific applications in the following areas: electrical insulation, marking and identification, protection (mechanical against corrosion), management and maintenance of wires.

## ADDITIONAL INFORMATION

Color and diameter next pages.

## LOGISTIC INFORMATION

### Packaging



#### No packaging

Height (cm) : 0.25  
 Length (cm) : 120  
 Depth (cm) : 0.25  
 Net weight (kg) : 0.00  
 Gross weight (kg) : 0.00



### Outer package 1



#### Bag

Height (cm) : 1.9  
 Length (cm) : 120  
 Depth (cm) : 0.4  
 Net weight (kg) : 0.02  
 Gross weight (kg) : 0.03

x 10



### Outer package 2



#### Carton box

Height (cm) : 8  
 Length (cm) : 130  
 Depth (cm) : 20  
 Net weight (kg) : 3  
 Gross weight (kg) : 3.8



x 750

### Outer package 3



#### Pallet

Height (cm) : 115  
 Length (cm) : 130  
 Depth (cm) : 80  
 Net weight (kg) : 168  
 Gross weight (kg) : 210

x 42000

