

Black 2/1 thin wall heat-shrink tubing without glue 3.5/1.8 mm 4 ft



Characteristics

Colour : **Black**
 Wall Ø before shrinking (mm) : **3.5**
 Wall Ø after shrinking (mm) : **1.8**

GENERAL INFORMATION

Description

Thin wall 2/1 heat-shrink tubing without adhesive.

Technical details

Thin wall, 2/1 shrinkage in length 1.2 meter.
 Heat-shrink tubing in flexible flame retardant polyolefin (except clear).
 Working temperature: -45 °C to +125 °C (clear is -45 °C to +105 °C).
 Shrink temperature: 120 °C (clear is 105 °C).
 Dielectric strength (IEC 243): 15 kV/mm.
 Tensile strength: 10.4 Mpa.
 Rate voltage: 600 V.
 Self-extinguishing in accordance with UL224 (except clear).

Application(s)

For general and specific applications in the following areas: electrical insulation, marking and identification, protection (mechanical against corrosion), management and maintenance of wires.

ADDITIONAL INFORMATION

Color and diameter next pages.

LOGISTIC INFORMATION

Packaging



No packaging

Height (cm) : 0.35
 Length (cm) : 120
 Depth (cm) : 0.35
 Net weight (kg) : 0.00
 Gross weight (kg) : 0.00



Outer package 1



Bag

Height (cm) : 2.6
 Length (cm) : 120
 Depth (cm) : 0.5
 Net weight (kg) : 0.03
 Gross weight (kg) : 0.04

x 10



Outer package 2



Carton box

Height (cm) : 8
 Length (cm) : 130
 Depth (cm) : 20
 Net weight (kg) : 3
 Gross weight (kg) : 3.5



x 500

Outer package 3



Pallet

Height (cm) : 115
 Length (cm) : 130
 Depth (cm) : 80
 Net weight (kg) : 168
 Gross weight (kg) : 196

x 28000

