

# Perforated zinc plated metal half saddles Ø 40 mm (x 50)



## Characteristics

**Ø (mm) : 40**  
**Ø1 (mm) : 6.2**  
**H (mm) : 43**  
**L (mm) : 80**  
**L1 (mm) : 66.2**  
**W (mm) : 31.9**  
**Thickness (mm) : 1.2**  
**Quantity per box : 50**  
**Selling unit : Each**

## Benefits

- Quick and easy installation: "Clips" feature for snapping and positioning the saddles onto conduit before securing it.
- Reinforced rib for extra strength.

## GENERAL INFORMATION

### Technical details

Material: steel Q235.  
Coating: blue-white zinc galvanized, ≥ 5 µm.

### Application(s)

Used to secure and mount electrical cables and conduits to a variety of work surfaces.  
For indoor and outdoor application.

## LOGISTIC INFORMATION

### Packaging



#### Plastic box

**Height (cm) : 12.3**  
**Length (cm) : 16.5**  
**Depth (cm) : 12**  
**Net weight (kg) : 1.84**  
**Gross weight (kg) : 1.94**



### Outer package 1



#### Carton box

**Height (cm) : 14**  
**Length (cm) : 62**  
**Depth (cm) : 35**  
**Net weight (kg) : 19**  
**Gross weight (kg) : 20**



x 10.00

### Outer package 2



#### Pallet

**Height (cm) : 130**  
**Length (cm) : 120**  
**Depth (cm) : 80**  
**Net weight (kg) : 673**  
**Gross weight (kg) : 679**



x 330.00