



HANDLE P S1 RED I-O METLVR

- Double break per pole offers high durability and short-circuit withstand
- Use of glass fibre reinforced polyester provides high mechanical and thermal resistance (does not include SLBM or VLBM modular series)
- Quick and easy to install thanks to good centre to centre distance and connection accessories including copper connecting links.
- Wide range of accessories available which is flexible in adapting to various applications and reduces the cost of management and storage
- All Socomec load break switches are compatible with the ergonomic IP65 S-Type Handles which features interlocking (in the ON position), padlocking, UV and chemical agent resistive material and the choice of standard blue or red / yellow colour

Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

Component Type	Power Distribution & Protection	Handle
Current, Rated Operational Current, AC-21a, 415V		63 A@415V
Details, Switch		SLB 16...160A or SSF 20...63A
Handle Type		Padlockable type
Colour, Bezel		Yellow
Colour, Handle		Red & Yellow colour
Details, text		S1 type handle
IP Rating		IP65
Padlockable		Yes

REFERENCES

IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	141E2911_Manufacturer Product Selection Guide