

# Catalogue No: **194R-N60-1753**

## LOAD BREAK SWITCH UL 194R 3P 60A

Power Distribution and Protection > Isolators and Transfer Switches > Load Break Switches > Allen-Bradley Load Break Switches > 194R - Non Fused Disconnect Switches > 3 Pole



### Load Break Switch UL 194R 3P 60A

- Suitable as At-Motor Disconnect Switch (UL508) useful for overseas application with added UL requirements
- Bulletin 194R also suitable as service entrance disconnecting (UL98) providing even greater application use
- Greater installation flexibility with selection of front/door or DIN/base mounting configurations (194E series only)
- Padlockable Handles Available (up to 3 padlocks) for added security
- Wide range of accessories available which is flexible in adapting to various applications and reduces the cost of management and storage

Representative Photo Only  
(actual product may vary based on configuration selections)

#### SPECIFICATIONS

Product Series	Bul. 194R
Number of Poles	3
Cable Cross Section (Min)	2.5 mm <sup>2</sup> mm
Cable Cross Section (Max)	25 mm <sup>2</sup> mm
Height	248 mm
Width	197 mm
Standards Compliance	UL 508 CSA C22.2 No. 14 IEC 60947-3 UL 98
Depth	111 mm
Weight	1.14 kg
Operating Effort	3.5 Nm
Operating Temperature, Min	-20 °C min
Operating Temperature, Max	60 °C max
Storage Temperature, Min	-40 °C min
Storage Temperature, Max	65 °C max
Relative humidity, min	50 %RH
Relative Humidity, Max	95 %RH
Certifications	CE

Catalogue No: **194R-N60-1753**

**LOAD BREAK SWITCH UL 194R 3P 60A**

Power Distribution and Protection > Isolators and Transfer Switches > Load Break Switches > Allen-Bradley Load Break Switches > 194R - Non Fused Disconnect Switches > 3 Pole



#### REFERENCES

IECEX Certificate -

Supplier Declaration of  
Conformity: -

Installation Guide: -

User Manual: -

Manufacturer Datasheet: -

Manufacturer Catalogue  
& Product Selection: -