

Catalogue No: **281-623**

## SCREWLESS TERMINAL FUSE DIS 4mm W/O BLW FUSE 1/4inX5/4in10A

Termination and Wiring Systems > Terminals and Pre-Wired Cables > Terminals - Screwless > WAGO Screwless Terminals > Series 281 - 4mm<sup>2</sup> Fuse Disconnect Terminal Blocks > Fuse Disconnect Terminal Blocks Supplied with Fuse

**NHP**



Representative Photo Only  
(actual product may vary based on configuration selections)

### Terminal Fuse Disconnect 4mm Grey

- Self-contained cage clamp assembly allows for quick and easy wire termination while ensuring contact quality
- Cage clamp terminals developed to suit a wide range of wire cross sections from 0.08 – 35mm<sup>2</sup>
- Alternate or staggered jumpers made in the field by simply breaking and removing jumper contacts
- Wide variety of terminal sizes and configurations including multiple conductors and decks, earth, sensor, high-current, fused and disconnect terminals
- Modular PCB terminal strips with cage clamp connection in various sizes and pin-spacing to suit any PCB solution
- Multi-connection system and WINSTA plugs and sockets suitable for lighting, power, and control connections
- Full range of accessories to complement any wire-termination solution

#### SPECIFICATIONS

Product Series	281
Component Type Termination Wiring	Terminal
Number of Conductors	2 qty
Number of Potentials	2
Connection / Termination	Cage Clamp Terminal(s)
Colour, Body / Housing	Grey colour
Conductor Entry Position	Front
Conductor Entry Angle	Angled
Wire / Conductor Size, Rigid Cable, Min	0.08 mm <sup>2</sup> min
Wire / Conductor Size, Rigid Cable, Max	4 mm <sup>2</sup> max
Wire / Conductor Size, Flex Cable, Min	0.08 mm <sup>2</sup> min
Wire / Conductor Size, Flex Cable, Max	4 mm <sup>2</sup> max
Wire Strip Length, Min	9 mm
Wire Strip Length, Max	10 mm
In, Rated Current	10 A
Un, Nominal Voltage	800 V
Rated surge voltage	8 kV
Pollution Degree	3
Marking Position	Centre
Fire Load	0.387 MJ
Mounting	DIN-35 Rail Mount
Details, Safety	Both nominal voltage and current are given by the fuse.
Ex i Suitable	No
IECEX Certified	No
Height	60 mm
Width	10 mm
Depth	60 mm
Weight	0.019474 kg

Catalogue No: **281-623**

**SCREWLESS TERMINAL FUSE DIS 4mm W/O BLW FUSE 1/4inX5/4in10A**

Termination and Wiring Systems > Terminals and Pre-Wired Cables > Terminals - Screwless > WAGO Screwless Terminals > Series 281 - 4mm<sup>2</sup> Fuse Disconnect Terminal Blocks > Fuse Disconnect Terminal Blocks Supplied with Fuse



Certifications

CCA  
CSA  
KEMA  
RoHS  
UL

Shipping Approvals

ABS (American Bureau of Shipping)  
BV (Bureau Veritas)  
PRS (Polish Register of Shipping)

**REFERENCES**

IECEX Certificate -

Supplier Declaration of Conformity: -

Installation Guide: -

User Manual: -

Manufacturer Datasheet: -

Manufacturer Catalogue & Product Selection: [281623\\_Manufacturer Catalogue](#)