


Switched transversely



Representative Photo Only
(actual product may vary based on configuration selections)

- Self-contained cage clamp assembly allows for quick and easy wire termination while ensuring contact quality
- Cage clamp terminals developed to suit a wide range of wire cross sections from 0.08 – 35mm²
- Alternate or staggered jumpers made in the field by simply breaking and removing jumper contacts
- Wide variety of terminal sizes and configurations including multiple conductors and decks, earth, sensor, high-current, fused and disconnect terminals
- Modular PCB terminal strips with cage clamp connection in various sizes and pin-spacing to suit any PCB solution
- Multi-connection system and WINSTA plugs and sockets suitable for lighting, power, and control connections
- Full range of accessories to complement any wire-termination solution

SPECIFICATIONS

Product Series	282
Component Type Termination Wiring	Terminal
Number of Conductors	2 qty
Number of Potentials	2
Connection / Termination	Cage Clamp Terminal(s)
Colour, Body / Housing	Grey colour
Conductor Entry Position	Front
Conductor Entry Angle	Angled
Wire / Conductor Size, Rigid Cable, Min	0.20 mm ² min
Wire / Conductor Size, Rigid Cable, Max	6 mm ² max
Wire / Conductor Size, Flex Cable, Min	0.20 mm ² min
Wire / Conductor Size, Flex Cable, Max	6 mm ² max
Wire Strip Length, Min	12 mm
Wire Strip Length, Max	13 mm
In, Rated Current	30 A
Un, Nominal Voltage	500 V
Rated surge voltage	6 kV
Pollution Degree	3
Marking Position	Centre / Side
Mounting	DIN-35 Rail Mount
Ex i Suitable	No
IECEX Certified	No
Height	89 mm
Width	8 mm
Depth	37.5 mm
Weight	0.017631 kg

Catalogue No: **282-811**

SCREWLESS TERMINAL DISCONNECT/TEST 6mm 2 CON TRANS 32A GREY

Termination and Wiring Systems > Terminals and Pre-Wired Cables > Terminals - Screwless > WAGO Screwless Terminals > Series 282 - 6mm² Cage Clamp Disconnect Test Terminal



Certifications

CCA
CSA
KEMA
RoHS
UL

Shipping Approvals

ABS (American Bureau of Shipping)
PRS (Polish Register of Shipping)

REFERENCES

IECEX Certificate -

Supplier Declaration of Conformity: -

Installation Guide: -

User Manual: -

Manufacturer Datasheet: -

Manufacturer Catalogue & Product Selection: [282811_Manufacturer Catalogue](#)

