

Catalogue No: 440G-T27256

TLS2 GD2 PWR TO LOCK 1NO/1NC 24V AC/DC FLX-ACT M20

Safety > Safety Interlocks > Mechanical Interlocks > Allen-Bradley 440G GuardLocking Switches > TLS-GD2



Guard Locking Switch - TLS-GD2: Solenoid Voltage: 24V AC/DC, Contacts(Safety and Aux): 2 Normally Closed, 1 Normally Open, Actuator: Fully-Flex, Conduit Entry: M20 Conduit



Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

Interlock Type	Guard locking switch
Safety Switch Type	Guard Locking Switch type
Interlock Type	Guard Locking Switch type
Number of Safety Contacts	2 qty safety
Output Configuration, Safety	2 NC
Number of Aux Contacts	1
Output Configuration, Auxiliary	1 NO
Solenoid Voltage, AC, Nom	24 V AC
Solenoid Voltage, AC/DC, Nom	24 V AC/DC
Holding Force, Max	2000 N
Conduit Entry	1 x M20 entry
Actuator Included	Yes Y / N
Actuator Type	Fully flexible tongue
Includes actuator guide	Yes Y / N
Un, Nominal Operational Voltage, AC	24 V AC
Un, Nominal Operational Voltage, DC	24 V DC
Material, Body / Housing	Glass-Filled PBT / Valox material
Ex Rated	No
Operating Temperature, Max	60 °C max
Operating Temperature, Min	-25 °C min
Storage Temperature, Max	60 °C max
Storage Temperature, Min	-25 °C min
IP Rating	IP67 IP69K

Catalogue No: **440G-T27256**

TLS2 GD2 PWR TO LOCK 1NO/1NC 24V AC/DC FLX-ACT M20

Safety > Safety Interlocks > Mechanical Interlocks > Allen-Bradley 440G GuardLocking Switches > TLS-GD2



REFERENCES	
IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-