

Catalogue No: **563420**

**EARTH BRAID 290A 70mm<sup>2</sup> LENGTH 300mm HOLE DIAMETER 12.5mm**

Power Distribution and Protection > Busbar, Chassis and Power Connections > Flexible Busbar and Braids > Eriflex  
Flexible Busbar and Braid > Earth Braid > Type MBJ



### Earth Braid 290A 70mm<sup>2</sup> Length 300mm

- Maximum working temperature 105°C
- Very good resistance to vibration and fatigue
- Ideal for earthing cabinet doors



Representative Photo Only  
(actual product may vary based on configuration selections)

#### SPECIFICATIONS

Component Type, Flexible Busbar and Braid Type	Braid
In, Rated Current	290 A
Material, Wire / Conductor	Copper
Material, cable jacket	Metal material
Wire / Conductor Size	70 mm <sup>2</sup>
Package Quantity	10 qty
Material Thickness, Conductor	3.4 mm
Length	300 mm
Width	28 mm
Weight	0.21 kg
Diameter, Mounting Hole(s)	12.5 mm
Operating Temperature, Max	105 °C max
Standards Compliance	IEC 61439-1-4
Certifications	C-UL-US Functional Safety Listed RoHS GOST

#### REFERENCES

IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-