

Catalogue No: **AE20M-24**

BUZZER PANEL MOUNT 90dB 50/60Hz IP55 24V AC/DC

Signalling Devices > Sound Indication > Buzzers, Hooters and Bells > Moflash Buzzers, Hooters and Bells > Buzzer > AE20M Miniature Buzzers



Representative Photo Only
(actual product may vary based on configuration selections)

Panel mount electronic buzzer, 24V DC IP55 Can be wired for Pulsed or Continuous tone

- Wide range including piezo-electric buzzers, motor driven hooters and mechanical bells to suit all requirements
- Piezo buzzers can be visually discreet and produce constant frequency output from 80 to 110dB dependent on model which is perfectly suited to simple signalling applications
- Motor driven hooters provide moderate dB output with an extremely recognizable sound
- Mechanical bells provide the traditional school bell sound in a sturdy construction that will stand the test of time

SPECIFICATIONS

IP Rating	IP55
Ue, Rated Operational Voltage, DC, min	10 V DC
Ue, Rated Operational Voltage, DC, max	28 V DC
In, Rated Current	0.025 A
Sound Mode	Continuous / Pulsed mode
Sound Level @1m	85 dB @1m
Material	ABS
Operating Temperature, Min	-20 °C min
Operating Temperature, Max	60 °C max

REFERENCES

IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-