

CA740M22240VAC

S&S CA7 Contactor 20kW 4Pole 240VAC Coil 2NO 2NC Contact Auxiliary



Component type	Power contactor, AC switching
Range	CA7
Model	N/A
Product status	Existing

The Sprecher + Schuh CA7 contactors are the ideal solution for reliable and durable electrical components. It is a modern and flexible IEC power contactor for DOL starting needs with up to 100A AC3 and wide range selection covering from 4kW up to 63kW (400V).

ELECTRICAL

Number of normally open contacts as main contact	2.0
Number of normally closed contacts as main contact	2.0
Rated operation current I_e at AC-3, 400 V	37.0 A
Rated operation power at AC-3, 400 V	18.5 kW
Rated operation current I_e at AC-1, 400 V	75.0 A
Max. rated operation voltage U_e AC	690.0 V
Voltage type for actuating	AC
Control supply voltage U_s at AC 50HZ	240.0 V
Number of auxiliary contacts as normally open contact	0.0
Number of auxiliary contacts as normally closed contact	0.0
Rated operation current I_e at AC-3, 690 V	9.0 A
Rated operation power at AC-3, 690 V	7.5 kW
Control supply voltage U_s at AC 60HZ	277.0 V
Power consumption, AC coil pickup	135.0 VA
Power consumption, AC coil hold-in	13.3 VA
Type of electrical connection of main circuit	Screw connection

CONSTRUCTION

Degree of protection (IP)	IP20
Mounting method	DIN-rail/screw

DIMENSIONS

Height	81.0 mm
Width	59.0 mm
Depth	107.0 mm
Weight	0.63 kg

CA740M22240VAC

S&S CA7 Contactor 20kW 4Pole 240VAC Coil 2NO 2NC Contact
Auxiliary

DIMENSIONAL DIAGRAM

