


Catalogue No: **CT8-A40**
OVERLOAD THERMAL 0.25-0.4A

Motor Control and Drives > Motor Starting and Protection > Motor Protection > Sprecher + Schuh Overloads > Thermal (Bi-Metallic) Overloads > CT8 Thermal Overloads



Representative Photo Only
(actual product may vary based on configuration selections)

Mini Thermal Overload Relay, 0.25...0.4A, 0.12kW, for use with CA 8-5, Trip Class 10A, Auto/Manual Reset

- Consistent and reliable protection for peace of mind
- Differential release for phase loss sensitivity and protection of motors in phase loss conditions
- Ambient temperature compensation from -20°C to +60°C for consistent performance

SPECIFICATIONS

Component Type Motor Control and Drives	Thermal Overload
Adjustment	1.5 : 1
Current Range (A)	0.25...0.40
Approx kW	0.12
Details, Contactor	CA8-5...12
Trip Class	10A
Reset	Automatic / Manual
Contact Configuration	1 NO + 1 NC
Test Function	Yes
Visible Trip Indicator	Yes
Motor FLC, Max	0.4 A, max
Motor FLC, Min	0.25 A, min
Rated Operation Voltage	690 V AC


REFERENCES

IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-


Catalogue No: **CT8-A40**

OVERLOAD THERMAL 0.25-0.4A

Motor Control and Drives > Motor Starting and Protection > Motor Protection > Sprecher + Schuh Overloads > Thermal (Bi-Metallic) Overloads > CT8 Thermal Overloads



Connection Diagrams



Connection / Wiring Diagram