

Catalogue No: **ESSS1253P**

ENCLOSED STAINLESS ESS 32BR 3P 125A

Power Distribution and Protection > Isolators and Transfer Switches > Enclosed Isolating Switches > Socomec Enclosed Isolating Switches > ESS Enclosed Stainless Steel Load Break Switches > 3P ESS Enclosed 32BR Load Break Switches



Representative Photo Only
(actual product may vary based on configuration selections)

ENCL SIDER SW 125A 3P SML

- Using 32BR32 safety visual load break switches
- 50 to 800A in 3 and 4 pole
- Flag indication through window
- "S" handle with metal locking lever standard
- Interlock prevents door opening when switch is ON
- Interlock prevents switch operation when door is open
- Earth and Neutral Bars included
- Optional aluminium handle
- Optional stainless steel handle (extra wide enclosure needed)

SPECIFICATIONS

Product Series	ESS
Component Type Power Distribution & Protection	Enclosed Isolating Switch
Number of Poles	3
In, Rated Current	125 A
IP Rating	IP65
Material, Body / Housing	Stainless Steel material
Colour, Handle	Red colour
Height	400 mm
Width	400 mm
Depth	210 mm
Standards Compliance	EN 60947-3 IEC 60947-3 UL 508 EN 61439 IEC 60364
Certifications	UL

REFERENCES

IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	ESSS1253P_Manufacturer Datasheet
Manufacturer Catalogue & Product Selection:	-