## Catalogue No: ISOSW320PRWLB

## SWITCH 3P 20A 500V AC RW LESS BACK BOX

Plugs, Sockets and Switches > Plugs and Sockets > Plugs and Sockets > ISO Plugs and Sockets > ISO Switches > Surface Switches (Less Back Box)





## Surface Switch 3 Pole 20A Resistant White No Back Box

- Large range covering 10 to 50A in 3, 4 and 5 pin configurations
- Components available: Switched Socket outlets, Switches, Socket Outlets, Plugs, Extension Sockets, Appliance Inlets, RCD Protected Outlets, Back Boxes and large range of accessories
- High ingress protection of IP66 across the range
- User friendly design with extruded ribbed grips, large switch handle and large socket latches for easy operation with or without gloves
- Suitable for most industrial and commercial applications
- Designed and tested to AS/NZS 3112 and AS/NZS 3123

| Representative Photo Only                                  |
|--|
| (actual product may vary based on configuration selections |

| SPECIFICATIONS                              |                                      |
|---|--------------------------------------|
| Product Series                              | ISO                                  |
| Component Type Plugs And Sockets            | Surface Switch                       |
| Un, Nominal Operational Voltage, AC         | 500 V AC                             |
| In, Rated Current                           | 20 A                                 |
| le, Rated Operational Current, AC-23a, 500V | 20 A@500V                            |
| IP Rating                                   | IP66                                 |
| Material, Body / Housing                    | Polycarbonate & PET Blend material   |
| Colour, Body / Housing                      | Resistant White colour               |
| Chemical Resistant Body / Housing           | Yes body                             |
| Details, Chemical Resistance                | Consult NHP                          |
| Wire / Conductor Size (Min)                 | 2.5 mm <sup>2</sup> min              |
| Wire / Conductor Size (Max)                 | 6 mm <sup>2</sup>                    |
| Switching Poles                             | 3P qty poles                         |
| Standards Compliance                        | AS/NZS 3112:2004<br>AS/NZS 3123:2005 |

| REFERENCES                                     |   |
|--|---|
| IECEx Certificate                              | - |
| Supplier Declaration of Conformity:            | - |
| Installation Guide:                            | - |
| User Manual:                                   | - |
| Manufacturer Datasheet:                        | - |
| Manufacturer Catalogue<br>& Product Selection: | - |

