

Catalogue No: **LE7-32-1753**

SWITCH LOAD 3P PANEL MOUNT 32A

Power Distribution and Protection > Isolators and Transfer Switches > Load Break Switches > Sprecher+Schuh Load Break Switches > LE7 Panel Mount > 3-Pole On-Off



Representative Photo Only
(actual product may vary based on configuration selections)

Load Break Switch, 3P, Panel Mount, 32A

- Rated currents up to 100A
- Touch-proof switch body (IP 20)
- Water spray and dustproof mechanism handles (IP 66)
- Easily accessible terminals
- Clearly marked terminals
- Wide range of accessories
- High AC 23 A ratings
- High breaking capacity
- Electronic compatibility of auxiliary contacts
- High short circuit withstand capacity (reduced risk of welding)
- High overvoltage withstand

SPECIFICATIONS

Number of Poles	3
Ui, Rated Insulation Voltage	690 V (rms)
Uimp, Impulse Withstand Voltage	690 kV
Icw, short time withstand current, 1s (rms)	0.9 kA for 1s
Ie, Rated Operational Current, AC-21a, 690V	32 A@690V
Ie, Rated Operational Current, DC-21a, 110V	32 A@110V
Ie, Rated Operational Current, DC-21a, 220V	15 A@220V
Ie, Rated Operational Current, DC-21a, 440V	2.2 A@440V
kW Rating, AC-23a, 400V, 3ph	15 kW @400V
kW Rating, AC-23a, 690V, 3ph	15 kW @690V
Tightening Torque, Max	12 Nm
Standards Compliance	IEC 60947-1 IEC 60947-3
Operating Temperature, Min	-25 °C min
Operating Temperature, Max	60 °C max
Storage Temperature, Min	-40 °C min
Storage Temperature, Max	80 °C max


Catalogue No: **LE7-32-1753**
SWITCH LOAD 3P PANEL MOUNT 32A

Power Distribution and Protection > Isolators and Transfer Switches > Load Break Switches > Sprecher+Schuh Load Break Switches > LE7 Panel Mount > 3-Pole On-Off



REFERENCES	
IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-

LE 7 - panel mounted switches - 3 pole (16 ... 100 A)



Type	B1	B2	F	H	L
LE 7-16	-	-	36	63	51
LE 7-25/32	-	36	45	64	60
LE 7-40/63	48	36	54	72	74
LE 7-80/100	48	36	72	90	90


Control handles

Cat. No.	Q	P	B
LFS 2-A-4	48 x 48	28	36
LFS 2-E-4	48 x 48	28	48
LFS 2-A-6	64 x 64	28	48
LFS 2-E-6	64 x 64	28	48
LFS 7-N-4-175	54 X 54	28	28
LFS 2-N-6	67 x 67	34	48
LFS 2-G-6	67 x 67	34	48
LFS 7-G-4-175	54 X 54	28	28

Dimension Diagram

Catalogue No: **LE7-32-1753**
SWITCH LOAD 3P PANEL MOUNT 32A

Power Distribution and Protection > Isolators and Transfer Switches > Load Break Switches > Sprecher+Schuh Load Break Switches > LE7 Panel Mount > 3-Pole On-Off



Technical Diagram