Catalogue No: **LE7-80-1753**

SWITCH LOAD 3P PANEL MOUNT 80A

Power Distribution and Protection > Isolators and Transfer Switches > Load Break Switches > Sprecher+Schuh Load Break Switches > LE7 Panel Mount > 3-Pole On-Off





Representative Photo Only (actual product may vary based on configuration selections)

Load Break Switch, 3P, Panel Mount, 80A

- Rated currents up to 100A
- Touch-proof switch body (IP 20)
- Water spray and dustproof mechanism handles (IP 66)
- Easily accessible terminals
- Clearly marked terminals
- Wide range of accessories
- High AC 23 A ratings
- High breaking capacity
- Electronic compatibility of auxiliary contacts
- High short circuit withstand capacity (reduced risk of welding)
- High overvoltage withstand

SPECIFICATIONS	
Number of Poles	3
Icw, short time withstand current, 1s (rms)	2.5 kA for 1s
Ui, Rated Insulation Voltage	690 V (rms)
Uimp, Impulse Withstand Voltage	690 kV
le, Rated Operational Current, AC-21a, 690V	80 A@690V
le, Rated Operational Current, DC-21a, 110V	80 A@110V
le, Rated Operational Current, DC-21a, 220V	50 A@220V
Ie, Rated Operational Current, DC-21a, 440V	6.5 A@440V
kW Rating, AC-23a, 400V, 3ph	37 kW @400V
kW Rating, AC-23a, 690V, 3ph	37 kW @690V
Tightening Torque, Max	50 Nm
Standards Compliance	IEC 60947-1 IEC 60947-3
Operating Temperature, Min	-25 °C min
Operating Temperature, Max	60 °C max
Storage Temperature, Min	-40 °C min
Storage Temperature, Max	80 °C max



Catalogue No: **LE7-80-1753**


SWITCH LOAD 3P PANEL MOUNT 80A

Power Distribution and Protection > Isolators and Transfer Switches > Load Break Switches > Sprecher+Schuh Load Break Switches > LE7 Panel Mount > 3-Pole On-Off



REFERENCES	
IECEx Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-

LE 7 - panel mounted switches - 3 pole (16 ... 100 A)



Туре	B1	B2	F	Н	L
LE 7-16	-	-	36	63	51
LE 7-25/32	-	36	45	64	60
LE 7-40/63	48	36	54	72	74
LE 7-80/100	48	36	72	90	90

Control handles

Cat. No.	Q	P	В
LFS 2-A-4	48 x 48	28	36
LFS 2-E-4	48 x 48	28	48
LFS 2-A-6	64 x 64	28	48
LFS 2-E-6	64 x 64	28	48
LFS 7-N-4-175	54 X 54	28	28
LFS 2-N-6	67 x 67	34	48
LFS 2-G-6	67 x 67	34	48
LFS 7-G-4-175	54 X 54	28	28

Dimension Diagram



Catalogue No: **LE7-80-1753**SWITCH LOAD 3P PANEL MOUNT 80A

Power Distribution and Protection > Isolators and Transfer Switches > Load Break Switches > Sprecher+Schuh Load Break Switches > LE7 Panel Mount > 3-Pole On-Off



