Catalogue No: MFR 012

HYGROSTAT ALARM 35-95 RH% 1 C/O

Enclosures and Climate Control > Climate Control > Heaters and Regulating Devices > Anti-Condensation Heaters and Regulating Devices > Regulating Devices > Mechanical Hygrostats for Anti-Condensation Applications





Representative Photo Only (actual product may vary based on configuration selections)

Hygrostat Alarm 35-95 RH% 1 C/O

- A large range of thermostats (cooling and heating), hygrostats and hygrotherms for control of heating and cooling
- Pressure compensation devices to prevent build up of condensation in areas of rapid temperature rise, or high pressure spray
- Drainage device for the removal of excess moisture
- Contact NHP for a custom heating or cooling solution

SPECIFICATIONS	
	The same of the
Component Type Heaters Filter Fans Regulating Devices	Hygrostat
Permissible Air Velocity	15 m/sec
Application Type(s)	Heating
Setpoint Range(s)	35 95% RH
Switch Difference	4% RH (± 3% tolerance)
Contact Type	Changeover
Max. Switching Capacity	5A @ 250V AC, 20W @ DC (min. 20V AC/100mA)
Service Life, Contacts	50000 cycles
Optical Indicator	No Y/N
Mounting	DIN-35 Rail Mount
Material, Body / Housing	Plastic material
Colour, Body / Housing	Light Grey colour
Height	67 mm
Width	50 mm
Depth	38 mm
Weight	0.06 kg
IP Rating	IP20
Storage Temperature, Min	-40 °C min
Storage Temperature, Max	60 °C max
Operating Temperature, Min	0 °C min
Operating Temperature, Max	60 °C max
Relative Humidity, Max	95 %RH
Approvals	UL File no. E164102




Catalogue No: MFR 012

HYGROSTAT ALARM 35-95 RH% 1 C/O





REFERENCES	
IECEx Certificate	
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-







Catalogue No: MFR 012


HYGROSTAT ALARM 35-95 RH% 1 C/O











Technical Diagram

