

Catalogue No: **MOLED400-04R**
BEACON 144 LED ST/FL/ROT 115/230V AC RED

Signalling Devices > Sight Indication > Beacons > Moflash Beacons > LED Beacons > MOLED400/401 Series - LED beacons



LED Beacon 115/230V AC - Red Lens - with 4 Mode Flash Rate. Static, 60 Flashes Per Minute, Rotating mode: Single Column or Rotating mode: Twin Column

- Complete visual signalling range from high efficiency static or flashing LED's to high discharge Xenon beacons to rotating parabolic reflector beacons, we have the solution suitable for your application.
- Available in a variety of frame sizes and with accessories such as protective cages and brackets to cater to your mounting requirements.
- Multiple colour varieties available including Red, Green, Amber and Blue to convey whichever message is required.

Representative Photo Only
 (actual product may vary based on configuration selections)

SPECIFICATIONS

Product Series	LED400 / 401
Indication Mode(s)	Sight
Lamp Type	LED type
Number of LEDs	144
Colour, Lamp	Red colour
Illumination Mode	Steady / Flashing / Rotating
Ie, Rated Operational Current, Flashing, 115V AC	0.09 A@115VAC
Ie, Rated Operational Current, Rotating, 115V AC	0.12 A@115VAC
Ie, Rated Operational Current, Steady, 115V AC	0.17 A@115VAC
Ie, Rated Operational Current, Flashing, 230V AC	0.05 A@230VAC
Ie, Rated Operational Current, Rotating, 230V AC	0.06 A@230VAC
Ie, Rated Operational Current, Steady, 230V AC	0.1 A@230VAC
Speed, Rotation	140 RPM
Speed, Flash	60 per min
Un, Nominal Operational Voltage(s), AC	115 V AC 230
Input Frequency, Nom	50 / 60 Hz
Details, Current	Rated at 115V AC - Flashing 90mA , Rotating 120mA, Static 170mA. Rated at 230V AC - Flashing 50mA, Rotating 60mA, Static 100mA
Material, Base	ABS
Connection / Termination	Fixed (non-removable) Terminal Block
Number of Terminals	2 qty
Mounting, Terminal Block	Internal Mount
IP Rating	IP65
Mounting (Multiple)	Surface Mount Wall Mount
Weight	1 kg
Operating Temperature, Min	-25 °C min

Catalogue No: **MOLED400-04R**
BEACON 144 LED ST/FL/ROT 115/230V AC RED

Signalling Devices > Sight Indication > Beacons > Moflash Beacons > LED Beacons > MOLED400/401 Series - LED beacons



Operating Temperature, Max	45 °C max
Certifications	CE RoHS

REFERENCES	
IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	MOLED400-04R_Installation Instructions
User Manual:	-
Manufacturer Datasheet:	MOLED400-04R_ManufacturerDatasheet
Manufacturer Catalogue & Product Selection:	-

